

PERISTALTIC DOSING PUMP - KBPER



Features:



TYPE	PE 1.5
POWER SUPPLY	230 Vac 50/60 Hz
CONSUMPTION	8W
TUBING	SANTOPRENE 6,25x10,65mm (I.D.xO.D.)
FLOW ml/REV	2,5
FLOW RATE ml/min	25
FLOW RATE l/h	1,5
FLOW RATE gph	0,398
BACKPRESSURE	1,5 BAR
PUMP BODY MATERIAL	Polypropylene (PP)
PUMP COVER MATERIAL	Polycarbonate (PC)
ROLLERS MATERIAL	Polyoxymethylene (PTFE)
IP DEGREE	IP65
WEIGHT	0,69 Kg (0,97 lb)
DOSING	Fixed flow rate
OPERATING TEMPERATURE	5-50°C
STORAGE TEMPERATURE	-20÷60°C
CERTIFICATION	CE, EAC

INSTALLATION KIT

FOOT FILTER	Grid filter in PP with ceramic weight
NON RETURN VALVE	FPM Umbrella Non Return Valve
FIXING BRACKET	PC Wall bracket with screw and dowel
SUCTION/DELIVERY TUBING	4x6 PVC (2 m roll)/4x6 PE (2 m roll)
REDUCTION	M 1/2 - F 3/8

DIMENSION

